

BNPM/NCB/366/2023-24	BANK NOTE PAPER MILL INDIA PRIVATE LIMITED	SHEET 1 OF 1
	Tender for Upgradation of LAN (Local Area Network) Infrastructure at BNPM, Mysuru. CORRIGENDUM NO. 3	

CORRIGENDUM No. 3, DATED 05.01.2024

FOR

TENDER NO. BNPM/NCB/366/2023-24 dated 10.11.2023

**TENDER FOR UPGRADATION OF LAN (LOCAL AREA
NETWORK) INFRASTRUCTURE AT BNPM PLANT,
MYSURU**



BNPM/NCB/366/2023-24	BANK NOTE PAPER MILL INDIA PRIVATE LIMITED	SHEET 1 OF 1
	Tender for Upgradation of LAN (Local Area Network) Infrastructure at BNPM, Mysuru. CORRIGENDUM NO. 3	

1.0 SCOPE OF THIS CORRIGENDUM

- 1.1 This corrigendum dated 05.01.2024, is issued for,
- (a) The tender due date extension for submission of tender published on 10.11.2023.
 - (b) Clarifications to queries received against the tender.
- 1.2 Except for details mentioned herein, all other details contained in the tender no. BNPM/NCB/366/2023-24 dated 10.11.2023, shall remain applicable and unchanged.

2.0 REVISION TO THE TENDER:-

- 2.1 Clause no. 1.1 (a) is as below

Closing date and time for receipt of tenders **15-01-2024 - 1100 Hours**
Date and time of opening of Techno-commercial bid **15-01-2024 - 1130 Hours**

3.0 CLARIFICATIONS/AMENDMENTS TO THE TENDER:-

- 3.1 Clause no 1.1 (b) is clarified/revised/amended as given below. Clarifications/revisions/amendments made in Section VII – Technical Specifications will apply *mutatis mutandis* to Section VIII - Quality Control Requirements.



BNPM/NCB/366/2023-24		BANK NOTE PAPER MILL INDIA PRIVATE LIMITED			SHEET 1 OF 1
Tender for Upgradation of LAN (Local Area Network) Infrastructure at BNPM, Mysuru.					
CORRIGENDUM NO. 3					
S No	Tender Clause	Provision as per Corrigendum-1 dated 11.12.2023	Provision as per Corrigendum-2 dated 22.12.2023	Bidders Query (Request to change)	Revision/Amendment to tender terms & conditions
1.	<u>Section VII - Technical Specifications (Clause-15(a)(1): Core Switch - Switch Hardware):</u> 24 x 1/10G SFP+ ports, 12 x 1/10G Base-T ports, 4 x 40G QSFP+ ports with expansion capacity of 3 slots for future use to expand 1G, 10G, 40G & 100G for future scalability, Switch should work in non-blocking architecture at wire speed, redundant hot swappable power supplies. All types of SFP, stacking modules, Transceivers and relevant copper and Optical patch cords & power cables should be loaded as per functional drawing (as per proposed design / architecture).	<u>S No (3) of Corrigendum-1 (Pg. 8 of 14):</u> 24 x 1/10G SFP+ ports, 12 x 1/10G Base-T ports / SFP+ copper module ports , 4 x 40G/ 100G QSFP28 ports with expansion capacity of 3 slots for future use to expand 1G, 10G, 40G & 100G for future scalability, Switch should work in non-blocking architecture at wire speed, redundant hot swappable power supplies. All types of SFP, stacking modules, Transceivers and relevant copper and Optical patch cords & power cables should be loaded as per functional drawing (as per proposed design / architecture).	<u>S No 3.1 (2) of Corrigendum-2 (Pg. 3 of 3):</u> 24 x 10G SFP+ ports, 12 x 10G Base-T ports / SFP+ copper module ports, 4 x 40G/100G QSFP28 ports with expansion capacity of 3 slots for future use to expand 1G, 10G, 40G & 100G for future scalability, Switch should work in non-blocking architecture at wire speed, redundant hot swappable power supplies. All types of SFP, stacking modules, Transceivers and relevant copper and Optical patch cords & power cables should be loaded as per functional drawing (as per proposed design / architecture).	a. 24 x 10G SFP+ ports, 12 x 10G Base-T ports / SFP+ copper module ports, 4 x 40G/100G QSFP28 ports with expansion capacity of 1 slot for future use to expand 1G, 10G, 40G & 100G for future scalability, Switch should work in non-blocking architecture at wire speed, redundant hot swappable power supplies. All types of SFP, stacking modules, Transceivers and relevant copper and Optical patch cords & power cables should be loaded as per functional drawing (as per proposed design / architecture). b. Need to remove expansion capacity of 3 slots for future use.	24 x 10G SFP+ ports, 12 x 10G Base-T ports / SFP+ copper module ports, 4 x 40G/100G QSFP28 ports, Switch should work in non-locking architecture at wire speed, redundant hot swappable power supplies. All types of SFP, stacking modules, Transceivers and relevant copper and Optical patch cords & power cables should be loaded as per functional Drawing (as per proposed design / architecture).

