

ENQUIRY No: BNPM/ENQ/FIRE RESISTANT HOSE /033/2018-19

Start Date: 18.04.2018

Last Date: 25.04.2018

1. Scope of work:

Supply of **FIRE RESISTANT HOSE- as per the Technical Specification provided herewith in Annexure -1.**

2. Terms & Conditions:

S. No.	Particulars	Quantity
1.	Payment Terms & Mode of Payment	100% on receipt and acceptance of goods by the consignee at destination and on production of all required documents by the supplier. <u>Warranty certificate (if applicable) and NEFT/RTGS details shall be furnished along with invoice.</u>
2.	Price	1. Price should be inclusive of all taxes & duties. Price evaluation will be without GST , however the order value will be inclusive of GST. Price should be fixed & firm up to the completion of supply, No price variation is accepted. Price evaluation will be on overall price basis.
3.	Freight	Shall be included in quoted price.
4.	Packing & Forwarding	Shall be included in quoted price
5.	Delivery Terms	FOR, Bank Note Paper Mill India Private Limited, Mysore
6.	Warranty Period	1 year from the date of delivery of material.
7.	Warranty Certificate	Applicable
8.	Delivery Period	2 weeks from receipt of order.
9.	Material to be delivered at	Engineering Stores Bank Note Paper Mill India Private Limited Note Mudran Nagar Mysore 570 003
10.	Contact person in Engineering Stores	Mr. Ashutosh Kumar 0821 2401 486 Mr. Sunil Kumar 0821 2401 485



ANNEXURE -1

TECHNICAL SPECIFICATION:

FIRE RESISTANT HOSES

<u>ITEM</u>	<u>TECH. SPECIFICATION</u>
FIRE RESISITANT HOSES –FOR BOILER BURNER FURNACE OIL INLET & OUTLET ID – ¾”, WP - 105 BAR /1525 PSI, BOTH ENDS FITTED WITH FEMALE CONNECTOR DN 20 WITH CRIMPING. LENGTH 2 m EACH, QTY – 6 Nos	FJ DIN 20022 / EN 853 I SNDN20 ID ¾” WP 105 BAR / 1525 PSI , EXCEEDS SAE 100 R1 AT (3Q/13)= AS ISO 9001 -200 CERTIFIED COMPANY OR EQUIVALENT (STANDARDS ARE TO BE MENTIONED FOR EQUIVALENT MATERIAL)
FIRE RESISITANT HOSES – FOR BOILER OPH UNIT PUMP SUCTION -DIA – 25 mm, WP – 8.8 MPa/88 BAR, BOTH ENDS FITTED WITH FEMALE CONNECTOR DN 25 WITH CRIMPING. LENGTH 660 mm EACH, QTY – 6 Nos	PARKER NON SKIVE 421 SN -16 WP 8.8 MPa/88 BAR MSHA IC -272 /1 - SAE 100R1 AT -216, 25 mm (1)x1 W EN 853 /1 SN/25/DIN FIRE RESISTANT OR EQUIVALENT (STANDARDS ARE TO BE MENTIONED FOR EQUIVALENT MATERIAL)
FIRE RESISITANT HOSES - - FOR BOILER OPH UNIT PUMP - DISCHARGE- DIA -¾”, WP – 10.5MPa/ 105 BAR , BOTH ENDS FITTED WITH FEMALE CONNECTOR DN 20 WITH CRIMPING. LENGTH 2 m EACH, QTY – 6 Nos	PARKER NON SKIVE 421 SN -12 WP 10.5 MPa/105 BAR - SAE 100R1 AT -12, 19 mm (¾”) 1 W EN 853 /1 SN/19/DIN FIRE RESISTANT OR EQUIVALENT (STANDARDS ARE TO BE MENTIONED FOR EQUIVALENT MATERIAL)
CERTIFICATES TO BE SUBMITTED	WARRANTY CERTIFICATE , TEST CERTIFICATE

We hereby confirm that

We hereby confirm that the Bid submitted by us is as per the technical specification specified in Annexure -1 and if awarded material will be supplied as per the same specification only. If at any time it is found that the material supplied by us is not as per this technical specification then the delivered material will be replaced with actual material free of cost , if not replaced then BNPMIPL have the right to procure the material from other sources at the risk & cost of us.

Signature of bidder:.....

Name of the Firm:.....

Seal of the firm:



3. Price Bid Format :

S. No. (A)	Description (B)	HSN COD E	Qty. (C)	UOM (D)	Unit rate (Basic) - in Rs. (E)	Freight, P&F Charges (if any) - in Rs. (F)	Total Rate inclusive of Basic Rate, Freight, P&F charges- exclusive of GST (FOR, BNPM, Mysore) { G= (E+F)*C}
1	FIRE RESISITANT HOSES –FOR BOILER BURNER FURNACE OIL INLET & OUTLET ID – ¾”, WP - - 105 BAR /1525 PSI, BOTH ENDS FITTED WITH FEMALE CONNECTOR DN 20 WITH CRIMPING. LENGTH 2 m EACH – As per Technical specification , Annexure - 1		6	Nos			
2	FIRE RESISITANT HOSES – FOR BOILER OPH UNIT PUMP SUCTION -DIA – 25 mm, WP – 8.8 MPa/88 BAR, BOTH ENDS FITTED WITH FEMALE CONNECTOR DN 25 WITH CRIMPING. LENGTH 660 mm EACH- As per Technical specification , Annexure - 1		6	Nos			
3	FIRE RESISITANT HOSES - - FOR BOILER OPH UNIT PUMP - DISCHARGE- DIA -¾”, WP – 10.5MPa/ 105 BAR , BOTH ENDS FITTED WITH FEMALE CONNECTOR DN 20 WITH CRIMPING. LENGTH 2 m EACH, – As per Technical specification , Annexure - 1		6	Nos			
2	GST %			GST VALUE – in Rs.(H)			
3	GRAND TOTAL (INCLUSIVE OF GST)– in Rs. -(G+H)						
4	GRAND TOTAL(INCLUSIVE OF GST)– in words						



We hereby confirm that

2. We accept all terms & conditions mentioned in the enquiry.
3. Price quoted is inclusive of all taxes, duties, P&F, freight etc. on FOR, BNPM, Mysore basis.
4. In case of any discrepancy between value in words and figures, value in figures shall prevail.

Signature of bidder:.....

Name of the Firm:.....

Seal of the firm:

