

# TENDER ENQUIRY FOR SUPPLY OF BREAKER CONTROL SWITCHES & SELECTOR SWITCHES AT BNPM PLANT, MYSURU

#### This tender document contains 40 Pages

Tender Enquiry No.	BNPM/OTE/94/2024-25
Tender issuing date	27.05.2024
Pre-bid meeting date & time	Not Applicable
Due date & time for bid submission	10.06.2024 @ 11.00 Hours
Mode of bid submission	Online
Type of tender	OPEN TENDER ENQUIRY (OTE)
Tender Processing Fee	Rs.100/- + Taxes
Details of contact person	Deputy General Manager (SCM) 0821-240111/175/184/177

Registered & Corporate Office: Administrative Building Gate 1, Paper Mill Compound Note Mudran Nagar, Mysuru – 570 003 Telephone No. 0821 – 2401 111

e-mail: <a href="mailto:scm.tender@bnpmindia.com">scm.tender@bnpmindia.com</a>

website: www.bnpmindia.com



1. Tenders are invited from eligible and qualified tenderers for supply of following goods

S No	Item Description	UOM	Quantity
1.	Breaker Control Switch with Sequence Lock & LMD 32A,660V AC/DC  • Amps rating:32,  • Operating Voltage : 660V AC/DC,  • Mechanism Type: Spring return,  • Control Contacts:3Trip+3Close,  • Signal Contacts:1NAT+1NAC,  • Size:75x75mm  • Handle: Pistol Grip,  • Angle of throw:60 degree,  • Positions: Trip-Neutral-Close,  • Colour Combination: Grey F.P and Black Knob,  • Equivalent Model: Switron  SBC32P474/114219/J383JSL,  • Make: L&T  Salzer/Kaycee/Recom/GT/Switron/Any  equivalent	Nos.	2
2.	Breaker Control Switch with Spring Return 25A,500V AC/220V DC  • Amps rating: 25,  • Operating Voltage: 500V AC & 220V DC,  • Mechanism Type: Spring return,  • No. of electrical ways: 04(02 packets),  • Size:75x75mm,  • Handle:Pistol Grip,  • Angle of throw:60 degree,  • Positions:Trip-Neutral-Close,  • Color Combination: Grey F.P and Black Knob,  • Equivalent Model: Kaycee BCA02P006K144,  • Make:L&T  Salzer/Kaycee/Recom/GT/Switron/Any  equivalent	Nos.	30
3.	Isolator Control Switch with Spring Return 32A,660V AC/DC  • Amps rating: 32, • Operating Voltage: 660V AC/DC, • Mechanism Type: Spring return,	Nos.	3



	SECTION II - TERMS & CONDITIONS	<u>S</u>	
4.	<ul> <li>Control Contacts: 20pen+2 Close,</li> <li>Size:75x75mm,</li> <li>Handle: Pistol Grip,</li> <li>Angle of throw:60 degree,</li> <li>Positions: Open-Neutral-Close,</li> <li>Color Combination: Grey F.P and Black Knob,</li> <li>Equivalent Model: Switron SBC32P244R,</li> <li>Make: L&amp;T Salzer/Kaycee/Recom/GT/Switron/Any equivalent</li> <li>Voltmeter Selector Switch 6A/460V AC</li> <li>Type: Instrumentation Selector Switches,</li> <li>Amps Rating:6A,</li> <li>Operational Voltage:460V,</li> <li>Description:3 - Phase Line to Line,</li> <li>No. of Stages:2,</li> <li>Operating Quadrant:90degree,</li> <li>Mounting: Front Mounting (B13),</li> <li>Script Plate Marking:0FF/RY/YB/BR,</li> <li>Knobs and Handles: Flag Handle,</li> <li>Size:48x48mm,</li> <li>Colour Combination: Alluminium (silver) Foil Front Plate with Black Handle,</li> <li>Equivalent Model: L&amp;T Salzer S6-61312-B13-FHAB</li> <li>Make:L&amp;T Salzer/Kaycee/Recom/GT/Switron/Any equivalent</li> </ul>	Nos.	4
5.	<ul> <li>Voltmeter Selector Switch 10A/440V AC</li> <li>Type: Instrumentation Selector Switch,</li> <li>Amps Rating:10A,</li> <li>Operational Voltage:440V AC,</li> <li>No. of discs:3,</li> <li>No. of poles:3,</li> <li>Angle of throw:90 degree,</li> <li>No. of positions:4,</li> <li>Size:48x48mm,</li> <li>Back of panel mounting length:52mm,</li> <li>Mounting: Front(panel) Mounting,</li> <li>Script Plate Marking: OFF/RY/YB/BR,</li> <li>Color Combination: Grey F.P and Black Knob,</li> <li>Equivalent Model: Kaycee 3S39VP,</li> </ul>	Nos.	6



	SECTION II – TERMS & CONDITIONS	<u>S</u>	
	Make: L&T		
	Salzer/Kaycee/Recom/GT/Switron/Any		
	equivalent		
	Ammeter Selector Switch 10A/440V AC		
	Type: Instrumentation Selector Switch,		
	Amps Rating:10A,		
	<ul> <li>Operational Voltage:440V AC,</li> </ul>		
	• No. of discs:4,		
	• No. of poles:3,		
	<ul> <li>Angle of throw:90 degree,</li> </ul>		
	<ul> <li>No. of positions:4,</li> </ul>		
6.	• Size:48x48mm,	Nos.	6
	<ul> <li>Back of panel mounting length:62mm,</li> </ul>		
	<ul> <li>Mounting: Front(panel) Mounting,</li> </ul>		
	<ul> <li>Script Plate Marking: OFF/R/Y/B,</li> </ul>		
	<ul> <li>Colour Combination: Grey F.P and Black Knob,</li> </ul>		
	<ul> <li>Equivalent Model: Kaycee 4S39AP,</li> </ul>		
	Make: L&T		
	Salzer/Kaycee/Recom/GT/Switron/Any		
	equivalent		
	Ammeter Selector Switch 6A/460V AC		
	Type: Instrumentation Selector Switches,		
	• Amps Rating:6A,		
	Operational Voltage:460V,		
	Description: 1 Pole -3 Transformer with OFF,		
	No. of Stages:3		
	Operating Quadrant:90degree		
	Mounting: Front Mounting (B13),  Carint Plate Madding OFF (B. (W. (B. (B. (B. (B. (B. (B. (B. (B. (B. (B		
7.	Script Plate Marking: OFF/R/Y/B  Woods and Hondles Floor Hondles  Woods and Hondles	Nos.	4
	<ul><li>Knobs and Handles: Flag Handle,</li><li>Size:48x48mm</li></ul>		
	<ul> <li>Colour Combination: Aluminium (silver) Foil</li> <li>Front Plate with Black Handle,</li> </ul>		
	<ul> <li>Equivalent Model: L&amp;T Salzer S6-61325-B13- FHAB</li> </ul>		
	Make: L&T		
	Salzer/Kaycee/Recom/GT/Switron/Any		
	equivalent		
	Rotary Switch(OFF-ON) 16A,250V AC/DC		
	• Amps Rating:16A,		
8.	Operational Voltage:250V AC/DC,	Nos.	2
	<ul> <li>No. of poles:2,</li> </ul>		
	o. po,		



	SECTION II - TERMS & CONDITION	<u>S</u>	
	<ul> <li>No. of discs:3</li> <li>Angle of throw:90 degree,</li> <li>No. of positions:4,</li> <li>Size:64x64mm,</li> <li>Back of panel mounting length:22mm,</li> <li>Mounting: Back of panel flush mounting,</li> <li>Script Plate Marking: OFF/ON/DC Selector Switch,</li> <li>Colour Combination: Grey F.P and Black Knob,</li> <li>Equivalent Model: Kaycee RP123,</li> <li>Make :L&amp;T Salzer/Kaycee/Recom/GT/Switron/Any equivalent</li> </ul>		
9.	Rotary Cam Switch(Two Way No OFF) 10A/440V AC  Amps Rating:10A,  Operational Voltage:440V AC,  No. of discs:2,  No. of poles:2,  Size:48x48mm,  Back of panel mounting length:43mm,  Mounting: Front(panel) Mounting,  Script Plate Marking: Auto/manual,  Colour Combination: Grey F.P and Black Knob,  Equivalent Model: Kaycee 2S26B,  Make: L&T  Salzer/Kaycee/Recom/GT/Switron/Any equivalent	Nos.	2
10.	Rotary Switch (Two Way Without Off) 16A/250V AC  • Amps Rating:16A,  • Operational Voltage:250V AC,  • No. of poles:2,  • No. of discs:5,  • Angle of throw:90 degree,  • No. of positions:4,  • Type: Two way without off,  • Size:64x64mm,  • Back of panel mounting length:34mm,  • Mounting: Back of panel flush mounting,  • Script Plate Marking: OFF/ON/AC Selector Switch,  • Colour Combination: Grey F.P and Black Knob,	Nos.	2



	SECTION II – TERMS & CONDITIONS	<u>S</u>	
	<ul> <li>Equivalent Model: Kaycee SRP125A,</li> </ul>		
	Make: L&T		
	Salzer/Kaycee/Recom/GT/Switron/Any		
	equivalent		
	Rotary Cam Switch(ON-OFF) 10A/440V AC		
	<ul> <li>Amps Rating:10A,</li> </ul>		
	<ul> <li>Operational Voltage:440V AC,</li> </ul>		
	<ul><li>No. of poles:1,</li></ul>		
	• No. of discs:1,		
	<ul> <li>Angle of throw:60 degree,</li> </ul>		
	<ul> <li>No. of positions:2,</li> </ul>		
11.	<ul> <li>Type: Rotary Cam Switch,</li> </ul>	Nos.	2
11.	• Size:48x48mm,	1103.	2
	<ul> <li>Back of panel mounting length:33mm,</li> </ul>		
	<ul> <li>Script Plate Marking: OFF/ON,</li> </ul>		
	<ul> <li>Colour Combination: Grey F.P and Black Knob,</li> </ul>		
	<ul> <li>Equivalent Model: Kaycee 1S160,</li> </ul>		
	Make: L&T		
	Salzer/Kaycee/Recom/GT/Switron/Any		
	equivalent		
	Rotary Cam Switch (Three Way No OFF) 10A/440V AC		
	• Amps Rating:10A,		
	<ul> <li>Operational Voltage:440V AC,</li> </ul>		
	• No. of poles:2,		
	• No. of discs:3,		
	<ul> <li>Angle of throw:60 degree,</li> </ul>		
	<ul> <li>No. of positions:3,</li> </ul>		
12.	<ul> <li>Type: 3 Way NO OFF Switch,</li> </ul>	Nos.	2
	• Size:48x48mm,		
	Back of panel mounting length:52mm,		
	Script Plate Marking: Auto/Manual/Scada,		
	Colour Combination: Grey F.P and Black Knob,		
	• Equivalent Model: Kaycee 3S26C,		
	Make: L&T		
	Salzer/Kaycee/Recom/GT/Switron/Any		
	equivalent		
	Rotary Cam Switch (Two Way with OFF) 10A/440V AC		
	• Amps Rating: 10A,		
13.	Operational Voltage:440V AC,  No. of males 4.	Nos.	2
	• No. of poles:4,		
	• No. of discs:4,		
	• No. of positions:3,		



	SECTION II - TERMS & CONDITIONS	<u>S</u>	
14.	<ul> <li>Type: 2-Way with OFF Switch,</li> <li>Size:48x48mm,</li> <li>Back of panel mounting length:62mm,</li> <li>Script Plate Marking: Auto/OFF/Manual,</li> <li>Colour Combination: Grey F.P and Black Knob,</li> <li>Equivalent Model: Kaycee 4S46B0,</li> <li>Make: L&amp;T Salzer/Kaycee/Recom/GT/Switron/Any equivalent</li> <li>Rotary Cam Switch(ON-OFF) 16A/690V AC</li> <li>Isolator Switch,</li> <li>Type:Cam Operated Rotary Switch,</li> <li>Amps Rating:16A,</li> <li>Operational Voltage:690V AC,</li> <li>Description:2 Pole,</li> <li>No. of Stages:1,</li> <li>Operating Quadrant:90 degree,</li> <li>Script Plate marking: ON/OFF,</li> <li>Mounting: Front Mounting with Round padlock for 2 Position (B33),</li> <li>Size:65x65mm,</li> <li>Colour Combination: YR (Yellow/Red),</li> <li>IP Rating: IP 55 from front,</li> <li>Equivalent Model: L&amp;T Salzer S16-61192-B33-XXYR,</li> <li>Make: L&amp;T Salzer/Kaycee/Recom/GT/Switron/Any equivalent</li> </ul>	Nos.	2
15.	Rotary Cam Switch(Multi Step Switch without OFF)  Type:Cam Operated Rotary Switches, Amps Rating: 16A, Operational Voltage:690V, Duty Rating: AC-21A, Description:6 Pole - 3 Way, No. of Stages:9, Operating Quadrant:60 degree, Script Plate marking: Auto/Manual/Off, Mounting: Front Mounting (B03), Size:48x48mm, Colour Combination: YR (Yellow/Red), Knobs and Handles: Tear Drop Handle, Equivalent Model: L&T Salzer 61126-B03-TDYR,	Nos.	2



	<b>SECTION II – TERMS &amp; CONDITION</b>	<u>S</u>	
	<ul> <li>Make: L&amp;T Salzer/Kaycee/Recom/GT/Switron/Any equivalent</li> <li>Rotary Switch (Two Way without OFF) 16A/250V AC</li> <li>Amps Rating:16A,</li> <li>Operational Voltage:250V AC,</li> <li>No. of poles:2,</li> <li>No. of discs:3,</li> <li>Angle of throw:90 degree,</li> </ul>		
16.	<ul> <li>No. of positions:4,</li> <li>Type: Two way without off,</li> <li>Size:64x64mm,</li> <li>Back of panel mounting length:22mm,</li> <li>Mounting: Back of panel flush mounting,</li> <li>Script Plate Marking: OFF/ON/AC Selector Switch,</li> <li>Colour Combination: Grey F.P and Black Knob,</li> <li>Equivalent Model: Kaycee SRP123,</li> <li>Make: L&amp;T Salzer/Kaycee/Recom/GT/Switron/Any equivalent</li> </ul>	Nos.	2

#### 2. Procedure for bid submission:

#### A) ONLINE:

- a) Interested bidders may obtain further information about this requirement from the above office selling the documents. They may also visit our website <a href="https://www.tenderwizard.com/BNP">www.tenderwizard.com/BNP</a> mentioned above for further details.
- b) Aspiring Bidders/Contractors who have not registered in e-tendering should register through the website E Tendering (<a href="www.tenderwizard.com/BNP">www.tenderwizard.com/BNP</a>) for participating in the Online Tenders. The registration charges will be Rs. 500/- plus applicable taxes (per year) which needs to be paid through electronic mode only.
- c) For details, registration and e-payment, please visit e-tendering website <a href="https://www.tenderwizard.com/BNP">www.tenderwizard.com/BNP</a> or contact KEONICS help desk @ 080-40482000.
- d) Class III Digital Signature Certificate (DSC) is mandatory to participate in e-Tenders. Participating bidders/Contractors have to make sure that they have the valid DSC. If not, they can procure from any of the firm as approved by CCA.
- 3. The tenderer shall satisfy BNPMIPL that they are competent and authorized to submit tender



and/or to enter into a legally binding contract with the BNPMIPL. To this effect, any person giving a tender shall render documentary evidence that his signature on the tender submitted by him is legally binding upon himself, his firm or company as the case may be.

**4.** BNPM reserves the right to cancel the tender at any stage without assigning the reasons thereof.

\*\*\*\*\*\*\*\*\*\*



#### 1. Documents to be submitted:

- a) Signed copy of this document (All the pages).
- **b)** Filled price schedule as per Section III of this document.
- **c)** Technical details /datasheet for the enquired product (if applicable).
- **d)** Micro / Small Enterprise (Certificate issued by MSME)/UAM/NSIC certificate (If applicable).
- e) Manufacturing unit details (if any).
- **2. Price:** Price should be inclusive of P&F, Freight, Transit Insurance and GST. Price shall remain fixed & no price variation shall be accepted till completion of contract.
- **3. Terms of Payment:** 100% payment shall be made within 30 days after <u>receipt and acceptance of complete supply</u> at BNPM Plant, Mysuru, as per purchase order and on production of all required documents by the supplier. NEFT/RTGS details shall be furnished along with the Original Invoice.

#### 4. Delivery Terms & Delivery Address:

Delivery shall be made on F.O.R Basis, Bank Note Paper Mill India Pvt. Ltd., Mysore.

Engineering Stores, Bank Note Paper Mill India Pvt. Ltd., Note Mudran Nagar, Mysore - 570003. Stores contact details: 0821-2401476/486.

**5. Taxes:** All Taxes shall be as applicable in GST regime.

Payment of CGST, SGST, IGST & UTGST: The suppliers are required to adhere the following procedure in order to honour the payment against CGST, SGST, IGST & UTGST in the invoice.

- i) An invoice issued by the vendor for goods or services or both as applicable should be in accordance with the provisions of Sec 31 of the CGST Act & should contain all the prescribed information's in accordance with Chapter VI of CGST rules 2017.
- ii) A debit note issued if any, by the vendor should be in accordance with the provisions of Sec 34 of the CGST Act.
- iii) The vendor should mandatorily upload the aforementioned documents in respective GSTR, details of outward supplies of goods or services as applicable within the prescribed time under GST Act.
- iv) The vendor should provide the relevant documents to confirm the tax charged on the invoice has been paid to the credit of government after adjusting the ITC if any.

Notwithstanding the above, the supplier should provide indemnification as follows:

In the event of non-compliances with respect to GST Act & Rules by the successful bidder, the purchaser is allowed to adjust the GST amount from retention amount (either in BG or in cash) held by the company. If no amount is available for recovery, the successful bidder will refund the GST liability within 10 days from the date of GST reversal in GSTRN.



The above requirements are mandatory to claim any GST liability, falling which, the GST liability will not be paid /reimbursed/accepted.

# A. The bidder should consider the following points while quoting GST Rate in their bids:

- 1. In case of unregistered bidders, the rate and amount of GST shall be shown as "Nil".
- 2. In case of a compounding dealer, GST shall be quoted as "Nil" as compounded dealers cannot collect GST from the consumers. The price quoted therefore shall be construed as all inclusive.
- 3. In case of work contracts or pure labour contracts, the bidder shall quote single GST rate for the work.
- 4. In case of composite supplies, i.e., a supply consisting of one principal supply and other ancillary supplies, the supply will attract the GST Rate of the principal supply. For example, if Item A in the supply order is the major or principal supply and other items are ancillary supplies, the bidder shall quote the GST Rate applicable to the principal goods (i.e., Item A) being supplied.
- 5. In case of mixed supply, i.e., a combination of two or more individual goods made together for a single price (each of these items can be supplied separately and is not dependent on any other), the total supply will attract the GST rate of the item which has the highest rate of tax. For example, if Item A in the mixed supply attracts highest rate of tax, the bidder shall quote the GST rate applicable to item A for total mixed supply.
- 6. In case of supplies which are neither composite nor mixed supplies, the bidder shall quote the GST Rate applicable to each item of supply separately.
- 7. If there is any difference of opinion regarding classification in HSN code, the bidder should sought clarification/raise query within the given time from the date of tender and it would be clarified before submitting the bid. Once clarified then that will be final & binding and no deviation shall be granted.

# B. Other instructions for the bidders to claim any GST liability, failing which, the GST liability will not be paid/reimbursed/accepted:

- 1. Registered/compounding Contractor/supplier should produce GST Invoice containing all the particulars stated in Rule 46 of the CGST Rules, 2017 in accordance with the provisions of Section 31 of the CGST ACT.
- 2. The supplier should mandatorily update the invoice details in GSTR-1, details of outward supplies of goods or services within the prescribed time under GST Act
- 3. The Payment shall be made net of TDS as per the provisions of CGST/SGST/IGST Act.
- 4. Wherever there is difference in the amount admitted, the supplier may be directed to issue a Credit Note (in case of reduction in the Invoice value)/Debit Note (in case of increase in the Invoice value), and payment shall be released only after the receipt of such Debit or Credit Note
- 5. Supplier should provide the relevant documents to confirm the tax charged on the invoice has been paid to the credit of Government after adjusting with ITC, if any.



- 6. Supplier should provide indemnification as follows: "In the event of non-compliances with respect to GST ACT and Rules by the supplier, the supplier should refund the GST liability within 10 days from the date of GST reversal in GSTRN failing which the purchaser shall recover the GST amount from the retention amount (whether in BG or in Cash) held by the company".
- **6. Warranty:** The product supplied shall be under warranty for 12 months from the date of receipt of material at BNPM Plant, Mysore. Warranty certificate to be enclosed wherever applicable.
  - If the applicable warranty period is less than 12 months then the same has to be mentioned at the appropriate place provided at page no. 7 of this enquiry document.
- **7. Liquidated Damages (LD):** Liquidated damages shall be applicable at the rate of 0.5% per week or part thereof until actual delivery or performance, subject to a maximum deduction of 10% of the delayed good's /service's contract price.
- **8. Delay in supplier's performance:** Time for and the date specified in the contract or as extended for the delivery of the stores shall be deemed to be the essence of the contract and the supplier shall deliver the goods and perform the services under the contract within the time schedule specified by BNPM in the contract.
  - Any delay attributable to the supplier in maintaining its contractual obligations towards delivery of goods and performance of services shall render the supplier liable to any or all the following sanctions besides any administrative action such as (a) Imposition of liquidity damages; (b) Termination of contract for default.
- **9. Extension of Time:** If the contract is delayed in the progress of work by changes ordered in the work, or any clause which BNPM shall decide to justify the delay, then the time of completion shall be extended by a reasonable time.
  - If at any time during the currency of contract, the supplier encounters conditions hindering timely delivery of the goods and performance of services, the supplier shall promptly inform BNPM in writing about the same and its likely duration and make a request to BNPM for extension of the delivery schedule accordingly. On receiving the
  - supplier's communication, BNPM shall examine the situation as soon as possible and, at its discretion, may agree to extend the delivery schedule, with or without liquidated damages for completion of supplier's contractual obligations by issuing an amendment to the contract.
- **10.Rejection Replacement:** In case of supplies, materials not meeting our specification will be rejected outright and the rejected material shall be taken back within 7 days at the cost and risk of the supplier and replacement should be made within 15 days from the date of intimation. No payment shall be made for rejected item. If the material is not taken back within the stipulate period, BNPM reserves the right to dispose-off the material at the risk and expense of the vendor as per provision under Section IV: General conditions of contract.



**11.Risk Purchase Clause:** If the supplier fails to abide by the terms and conditions of the contract/agreement, or fails to supply the material as per the delivery schedule or any time repudiates the contract,

Procure the tendered item / render service from other agencies at the risk and cost of the supplier. The cost difference between the alternative arrangement and existing contract value wherein default has been made will be recovered from the supplier along with the other incidental charges.

In case of procurement through alternative sources, if procurement price is lower than the existing contract value wherein default has been made, in such case no benefit on this account will be passed on to the supplier.

- **12.Termination for Convenience (Foreclosure) Clause:** BNPM reserves the right to terminate the contract, in whole or in part for its (BNPM's) convenience, by serving written notice on the supplier at any time during the currency of the contract. The notice shall specify that the termination is for the convenience of BNPM. The notice shall also indicate inter-alia, the extent to which the supplier's performance under the contract is terminated, and the date with effect from which such termination will become effective.
- **13.Settlement of Disputes through Arbitration:** All disputes and differences of any kind whatsoever arising out of or in connection with the contract, whether during the progress of the work or after their completion except accepted matters shall be settled through arbitration process as per the Arbitration & Conciliation Act, 1996. The venue of arbitration shall be Mysore, Karnataka.
- **14.Legal Jurisdiction:** The Courts of Mysore (Karnataka State) shall alone have jurisdiction to decide on any legal matter of dispute whatsoever arising out or in respect of the contract.
- **15. Force Majeure:** In the event of any unforeseen event directly interfering with the supply of stores arising during the currency of the contract, such as war, hostilities, acts of the public enemy, civil commotion, sabotage, fires, floods, explosions, epidemics, quarantine restrictions, strikes, lockouts, or acts of God, the Contractor shall, within a week from the commencement thereof, notify the same in writing to the Purchaser with reasonable

evidence thereof. Unless otherwise directed by BNPM in writing, the supplier shall continue to perform its obligations under the contract as far as reasonably practical, and shall seek all reasonable alternative means for performance not prevented by the Force Majeure event. If the force majeure condition(s) mentioned above be in force for a period of 90 days or more at any time, either party shall have the option to terminate the contract on expiry of 90 days of commencement of such force majeure by giving 14 days' notice to the other party in writing. In case of such termination, no damages shall be claimed by either party against the other, save and except those which had occurred under any other clause of this contract prior to such termination.

**16.Fore-Closure Clause:** If at any time during the continuation of this contract, the use of material ordered in this contract is completely banned or due to drastic change in



Government policy its use as, raw material is discontinued or is declared hazardous to public health or cause rising to civil commotion, epidemics, wide-spread strikes and 21 days' notice of such eventualities is given by purchaser to the seller, the seller without any right to enforce the contract, will agree to the fore-close the performance of balance portion of this contract and in that event no claim for damages or loss will be lodged against the purchaser.

**17.Rights of Rejection:** BNPMIPL reserves the right to reject any or all the applied bids without assigning any reason whatsoever. The enquiry can be rejected on national security grounds.

#### 18. Note:

i. Catalogue/datasheet of the quoted products have to be provided



#### Tender No.: BNPM/OTE/94/2024-25 dated: 27.05.2024

Sch. No	Material Description	UOM	Qty	Offered Make (If applica ble)	Unit Price (INR)	P&F, Insuranc e & Freight Charges (INR)	GST@ Amount (INR)	Unit price including P&F, Insurance, Freight & GST (INR)	Total price inclusive of P&F, Insurance, Freight & GST (F.O.R, BNPM, Mysuru) (INR)	Input GST Credit (INR) {GST amount * Total quantity}	Effective price inclusive of P&F, Insuranc e, Freight (F.O.R, BNPM, Mysuru) (INR)
A	В	С	D		Е	F	G	H=E+F+G	I=H*D	J=G*D	K=I-J
1.	Breaker Control Switch with Sequence Lock & LMD 32A,660V AC/DC  • Amps rating:32, • Operating Voltage: 660V AC/DC, • Mechanism Type: Spring return, • Control Contacts:3Trip +3Close,	Nos.	2								



	<ul> <li>Signal         Contacts:1NAT         +1NAC,</li> <li>Size:75x75mm</li> <li>Handle: Pistol         Grip,</li> <li>Angle of         throw:60         degree,</li> <li>Positions: Trip-         Neutral-Close,</li> <li>Colour         Combination:         Grey F.P and         Black Knob,</li> <li>Equivalent</li> </ul>						
	SBC32P474/11 4219/J383JSL,  • Make: L&T Salzer/Kaycee/ Recom/GT/Swi tron/Any						
	equivalent						
2.	Breaker Control Switch with Spring Return 25A,500V AC/220V DC	Nos.	30				



Amps rating:					
25,					
<ul> <li>Operating</li> </ul>					
Voltage : 500V					
AC & 220V DC,					
<ul> <li>Mechanism</li> </ul>					
Type: Spring					
return,					
No. of electrical					
ways: 04(02					
packets),					
• Size:75x75mm,					
Handle:Pistol					
Grip,					
Angle of					
throw:60					
degree,					
Positions:Trip-					
Neutral-Close,					
• Color					
Combination:					
Grey F.P and					
Black Knob,					
Equivalent					
Model: Kaycee					
BCA02P006K1					
44,					



	Make:L&T						
	Salzer/Kaycee/						
	Recom/GT/Swi						
	tron/Any						
	equivalent						
	Isolator Control						
	Switch with Spring						
	Return 32A,660V						
	AC/DC						
	Amps rating:						
	32,						
	• Operating						
	Voltage: 660V						
	AC/ DC ,						
	Mechanism						
3.	Type: Spring	Nos.	3				
	return,						
	• Control						
	Contacts:						
	20pen+2 Close,						
	• Size:75x75mm,						
	Handle: Pistol						
	Grip,						
	Angle of						
	throw:60						
	degree,						

	<ul> <li>Positions:         <ul> <li>Open-Neutral-Close,</li> </ul> </li> <li>Color             <ul> <li>Combination:</li> <li>Grey F.P and</li> <li>Black Knob,</li> <li>Equivalent</li> <li>Model: Switron</li> <li>SBC32P244R,</li> <li>Make: L&amp;T</li> <li>Salzer/Kaycee/</li> <li>Dance (GT/Social</li> <li>Open-Neutral-Color</li> <li>Open-Neutral-Color</li> <li>Open-Neutral-Color</li> <li>Open-Neutral-Color</li> <li>Model: Switron</li> <li>SBC32P244R,</li> <li>Make: L&amp;T</li> <li>Salzer/Kaycee/</li> <li>Make: L&amp;T</li> <li>Make: L&amp;T</li></ul></li></ul>						
	Recom/GT/Swi tron/Any equivalent						
4.	Voltmeter Selector Switch 6A/460V AC  Type: Instrumentatio n Selector Switches, Amps Rating:6A, Operational Voltage:460V, Description:3 - Phase Line to Line,	Nos.	4				



I	N	1	T		
	• No. of Stages:2,				
	• Operating				
	Quadrant:90de				
	gree,				
	Mounting:				
	Front Mounting				
	(B13),				
	Script Plate				
	Marking:OFF/R				
	Y/YB/BR,				
	Knobs and				
	Handles: Flag				
	Handle,				
	• Size:48x48mm,				
	• Colour				
	Combination:				
	Alluminium				
	(silver) Foil				
	Front Plate				
	with Black				
	Handle,				
	• Equivalent				
	Model: L&T				
	Salzer S6-				
	61312-B13-				
	FHAB				
	Make:L&T				
	Salzer/Kaycee/				
	callet / hay ecc/				



	Recom/GT/Swi							
	tron/Any							
	equivalent							
	Voltmeter Selector							
	Switch 10A/440V AC							
	• Type:							
	Instrumentatio							
	n Selector							
	Switch,							
	<ul><li>Amps</li></ul>							
	Rating:10A,							
	<ul> <li>Operational</li> </ul>							
	Voltage:440V							
	AC,							
	• No. of discs:3,							
5.	• No. of poles:3,	Nos.	6					
	• Angle of							
	throw:90							
	degree,							
	• No. of							
	positions:4, • Size:48x48mm,							
	Back of panel     mounting							
	mounting length:52mm,							
	<ul><li>Mounting:</li></ul>							
	Front(panel)							
	Mounting,							
	Mounting,				1	]		



	Script Plate						
	Marking:						
	OFF/RY/YB/B						
	R,						
	• Color						
	Combination:						
	Grey F.P and						
	Black Knob,						
	<ul> <li>Equivalent</li> </ul>						
	Model: Kaycee						
	3S39VP,						
	<ul> <li>Make: L&amp;T</li> </ul>						
	Salzer/Kaycee/						
	Recom/GT/Swi						
	tron/Any						
	equivalent						
	Ammeter Selector						
	Switch 10A/440V AC						
	• Type:						
	Instrumentatio						
	n Selector						
			(				
6.	Switch,	Nos.	6				
	• Amps						
	Rating:10A,						
	<ul> <li>Operational</li> </ul>						
	Voltage:440V						
	AC,						



• No. of discs:4,					
<ul> <li>No. of poles:3,</li> </ul>					
Angle of					
throw:90					
degree,					
No. of					
positions:4,					
• Size:48x48mm,					
Back of panel					
mounting					
length:62mm,					
Mounting:					
Front(panel)					
Mounting,					
Script Plate					
Marking:					
OFF/R/Y/B,					
• Colour					
Combination:					
Grey F.P and					
Black Knob,					
Equivalent					
Model: Kaycee					
4S39AP,					
Make: L&T					
Salzer/Kaycee/					
Recom/GT/Swi					



	tron/Any						
	equivalent						
7.	Ammeter Selector Switch 6A/460V AC  Type: Instrumentatio n Selector Switches, Amps Rating:6A, Operational Voltage:460V, Description:1 Pole -3 Transformer with OFF, No. of Stages:3 Operating Quadrant:90de gree Mounting: Front Mounting (B13), Script Plate Marking: OFF/R/Y/B	Nos.	4				



	<ul> <li>Knobs and</li> </ul>						
	Handles: Flag						
	Handle,						
	• Size:48x48mm						
	<ul> <li>Colour</li> </ul>						
	Combination:						
	Aluminium						
	(silver) Foil						
	Front Plate						
	with Black						
	Handle,						
	<ul> <li>Equivalent</li> </ul>						
	Model: L&T						
	Salzer S6-						
	61325-B13-						
	FHAB						
	<ul><li>Make: L&amp;T</li></ul>						
	Salzer/Kaycee/						
	Recom/GT/Swi						
	tron/Any						
	equivalent						
	Rotary Switch(OFF-						
	ON) 16A,250V AC/DC						
	• Amps		•				
8.	Rating:16A,	Nos.	2				
	Operational     Operational						
	Voltage:250V						
	AC/DC,						



• No. of poles:2,				
• No. of discs:3				
Angle of				
throw:90				
degree,				
No. of				
positions:4,				
• Size:64x64mm,				
Back of panel				
mounting				
length:22mm,				
Mounting: Back				
of panel flush				
mounting,				
Script Plate				
Marking:				
OFF/ON/DC				
Selector				
Switch,				
• Colour				
Combination:				
Grey F.P and				
Black Knob,				
• Equivalent				
Model: Kaycee				
RP123,				



	Make :L&T     Salzer/Kaycee/     Recom/GT/Swi     tron/Any     equivalent						
9.	Rotary Cam Switch(Two Way No OFF) 10A/440V AC  Amps Rating:10A, Operational Voltage:440V AC, No. of discs:2, No. of poles:2, No. of positions:2, Size:48x48mm, Back of panel mounting length:43mm, Mounting: Front(panel) Mounting, Script Plate Marking: Auto/manual,	Nos.	2				



	• Colour						
	Combination:						
	Grey F.P and						
	Black Knob,						
	<ul> <li>Equivalent</li> </ul>						
	Model: Kaycee						
	2S26B,						
	<ul><li>Make: L&amp;T</li></ul>						
	Salzer/Kaycee/						
	Recom/GT/Swi						
	tron/Any						
	equivalent						
	Rotary Switch (Two						
	Way Without Off)						
	16A/250V AC						
	<ul><li>Amps</li></ul>						
	Rating:16A,						
	<ul> <li>Operational</li> </ul>						
	Voltage:250V						
10.	AC,	Nos.	2				
	• No. of poles:2,	11001	_				
	• No. of discs:5,						
	<ul><li>Angle of</li></ul>						
	throw:90						
	degree,						
	<ul><li>No. of</li></ul>						
	positions:4,						



					•
Type: Two way					
without off,					
• Size:64x64mm,					
Back of panel					
mounting					
length:34mm,					
Mounting: Back					
of panel flush					
mounting,					
Script Plate					
Marking:					
OFF/ON/AC					
Selector					
Switch,					
• Colour					
Combination:					
Grey F.P and					
Black Knob,					
<ul> <li>Equivalent</li> </ul>					
Model: Kaycee					
SRP125A,					
• Make: L&T					
Salzer/Kaycee/					
Recom/GT/Swi					
tron/Any					
equivalent					



	Rotary Cam						
	Switch(ON-OFF)						
	10A/440V AC						
	• Amps						
	Rating:10A,						
	<ul> <li>Operational</li> </ul>						
	Voltage:440V						
	AC,						
	<ul> <li>No. of poles:1,</li> </ul>						
	<ul> <li>No. of discs:1,</li> </ul>						
	<ul> <li>Angle of</li> </ul>						
	throw:60						
	degree,						
	• No of						
11.	positions:2,	Nos.	2				
	Type: Rotary						
	Cam Switch,						
	• Size:48x48mm,						
	Back of panel						
	mounting						
	length:33mm,						
	Script Plate						
	Marking:						
	OFF/ON,						
	• Colour						
	Combination:						
	Grey F.P and						
	Black Knob,						



<ul><li>Equivalent Model: Kaycee 1S160,</li><li>Make: L&amp;T</li></ul>						
Salzer/Kaycee/ Recom/GT/Swi tron/Any equivalent						
Rotary Cam Switch (Three Way No OFF)  10A/440V AC	Nos.	2				

	Back of panel						
	mounting						
	length:52mm,						
	<ul> <li>Script Plate</li> </ul>						
	Marking:						
	Auto/Manual/S						
	cada,						
	<ul> <li>Colour</li> </ul>						
	Combination:						
	Grey F.P and						
	Black Knob,						
	<ul> <li>Equivalent</li> </ul>						
	Model: Kaycee						
	3S26C,						
	<ul><li>Make: L&amp;T</li></ul>						
	Salzer/Kaycee/						
	Recom/GT/Swi						
	tron/Any						
	equivalent						
	Rotary Cam Switch						
	(Two Way with OFF)						
	10A/440V AC						
	• Amps						
13.	Rating:10A,	Nos.	2				
13.	<ul><li>Operational</li></ul>	NOS.					
	Voltage:440V						
	AC,						
	<ul> <li>No. of poles:4,</li> </ul>						



<ul> <li>No. of discs:4,</li> <li>No. of positions:3,</li> <li>Type: 2-Way with OFF Switch,</li> <li>Size:48x48mm,</li> <li>Back of panel mounting length:62mm,</li> <li>Script Plate Marking: Auto/OFF/Man ual,</li> </ul>	
positions:3,  Type: 2-Way with OFF Switch, Size:48x48mm, Back of panel mounting length:62mm, Script Plate Marking: Auto/OFF/Man	
<ul> <li>Type: 2-Way with 0FF Switch,</li> <li>Size:48x48mm,</li> <li>Back of panel mounting length:62mm,</li> <li>Script Plate Marking: Auto/0FF/Man</li> </ul>	
with OFF Switch, Size:48x48mm, Back of panel mounting length:62mm, Script Plate Marking: Auto/OFF/Man	
with OFF Switch, Size:48x48mm, Back of panel mounting length:62mm, Script Plate Marking: Auto/OFF/Man	
Switch, Size:48x48mm, Back of panel mounting length:62mm, Script Plate Marking: Auto/OFF/Man	
<ul> <li>Size:48x48mm,</li> <li>Back of panel mounting length:62mm,</li> <li>Script Plate Marking: Auto/OFF/Man</li> </ul>	
<ul> <li>Back of panel mounting length:62mm,</li> <li>Script Plate Marking: Auto/OFF/Man</li> </ul>	
mounting length:62mm,  • Script Plate Marking: Auto/OFF/Man	
length:62mm,  • Script Plate  Marking: Auto/OFF/Man	
• Script Plate Marking: Auto/OFF/Man	
Marking: Auto/OFF/Man	
Auto/OFF/Man Auto/OFF/Man	
• Colour	
Combination:	
Grey F.P and	
Black Knob,	
Equivalent	
Model: Kaycee	
4S46B0,	
Make: L&T	
Salzer/Kaycee/	
Recom/GT/Swi	
tron/Any tron/Any	
equivalent	



	Rotary Cam						
	Switch(ON-OFF)						
	16A/690V AC						
	<ul> <li>Isolator Switch,</li> </ul>						
	• Type:Cam						
	Operated						
	Rotary Switch,						
	<ul><li>Amps</li></ul>						
	Rating:16A,						
	<ul> <li>Operational</li> </ul>						
	Voltage:690V						
	AC,						
	• Description:2						
14.		Nos.	2				
	<ul><li>No. of Stages:1,</li></ul>						
	<ul> <li>Operating</li> </ul>						
	Quadrant:90						
	degree,						
	<ul> <li>Script Plate</li> </ul>						
	marking:						
	ON/OFF,						
	<ul><li>Mounting:</li></ul>						
	Front Mounting						
	with Round						
	padlock for 2						
	Position (B33),						
	• Size:65x65mm,						

	• Colour						
	Combination:						
	YR						
	(Yellow/Red),						
	<ul><li>IP Rating: IP 55</li></ul>						
	from front,						
	<ul> <li>Equivalent</li> </ul>						
	Model: L&T						
	Salzer S16-						
	61192-B33-						
	XXYR,						
	Make: L&T						
	Salzer/Kaycee/						
	Recom/GT/Swi						
	tron/Any						
	equivalent						
	Rotary Cam						
	Switch(Multi Step						
	Switch without OFF)						
	<ul><li>Type:Cam</li></ul>						
	Operated						
15.	Rotary	Nos.	2				
	Switches,						
	<ul><li>Amps Rating:</li></ul>						
	16A,						
	<ul> <li>Operational</li> </ul>						
	Voltage:690V,						



	 	 1	T	T	1	T
Duty Rating:						
AC-21A,						
• Description:6						
Pole - 3 Way,						
No. of Stages:9,						
Operating						
Quadrant:60						
degree,						
Script Plate						
marking:						
Auto/Manual/						
Off,						
Mounting:						
Front Mounting						
(B03),						
• Size:48x48mm,						
• Colour						
Combination:						
YR						
(Yellow/Red),						
Knobs and						
Handles: Tear						
Drop Handle,						
Equivalent						
Model: L&T						
Salzer 61126-						
B03-TDYR,						
,						
		i .	I		1	



	<ul> <li>Make: L&amp;T         Salzer/Kaycee/         Recom/GT/Swi         tron/Any         equivalent     </li> </ul>						
16.	equivalent  Rotary Switch (Two Way without OFF)  16A/250V AC  • Amps Rating:16A, • Operational Voltage:250V AC, • No. of poles:2, • No. of discs:3, • Angle of throw:90 degree, • No. of	Nos.	2				
	positions:4,     Type: Two way without off,     Size:64x64mm,     Back of panel mounting length:22mm,						



#### Mounting: Back of panel flush mounting, Script Plate Marking: OFF/ON/AC Selector Switch, Colour Combination: Grey F.P and Black Knob, Equivalent Model: Kaycee SRP123, Make: L&T Salzer/Kaycee/ Recom/GT/Swi tron/Any equivalent **Grand Total**

**SECTION III - PRICE SCHEDULE** 

#### Note:

- 1. Evaluation shall be done on the basis of **overall effective price** quoted by the bidder
- 2. When bidders are submitting bid through online mode (e-Tender portal), then they should submit price bid through tender wizard portal price bid format only.



# **SECTION IV – DECLARATION**

We he	ereby confirm that
	We accept all the terms & conditions mentioned in the enquiry.
2.	Price quoted is inclusive of P&F, Insurance, Freight and GST on F.O.R Basis, BNPM Plant
	Mysore.
3.	HSN Code: Item;
4.	GST registration status: Unregistered / compounding / registered.
5.	Delivery period: (Days / Weeks)
6.	Warranty Period: Months (Time Period to be specified in case warranty
	period is less than 12 months / NA to mentioned in the in-case warranty is not applicable)
7.	Bid validity: 90 days from date of closing of tender including extensions/ corrigendum's
	(if any). Bid Security declaration has been submitted as per format.
8.	Bank Details (Enclosed - Cancelled Cheque/ Bank Mandate):
	Bank Acc. No;
	Bank Acc Name:;
	Branch name:; Branch Code:;
	IFSC:;
9.	MSME / NSIC status: (If yes, then supporting document shall be
	submitted along with the offer to avail the benefits under the Procurement Policy for
	MSEs, Order 2012 along with its amendments.)
	(Please fill above: MSI – For Micro Enterprises; SSI – For Small Enterprises; MED.SI – For
	Medium Enterprises; NSIC – For National Small Industries Corporation regd. firm)
10	. Technical Data sheet/ Product Catalogue (Submitted/ Not submitted).
Signat	cure of bidder:
Name	of the Firm:
Seal o	f the firm:
GST N	O.:



**Contact Details: -**

Contact Person: .....

Contact Number: .....

#### **SECTION IV - DECLARATION**

Tender No.: BNPM/OTE/94/2024-25 dated: 27.05.2024

(To be submitted on Company letterhead)

#### **BID SECURITY DECLARATION**

We, the undersigned, declare that we will automatically be suspended from being eligible for bidding in any tender with Bank Paper Mill India Private Limited, Mysore for the period of 12 months, if we are withdrawing our Bid during the period of bid validity (or) fail / refuse to furnish the performance security / execute the contract, if awarded.

Signature
Name
Designation
Date
Stamp of the Organization

