

ENQUIRY No: BNPM/ENQ/Pressure Gauges/323/2017-18

Star Date: 06.12.2017

Last Date: 14.12.2017

Extended Upto: 18.12.2017

Closing Time: 1000Hrs

1. Scope of work:

Supply of **Pressure Gauges**

2. Terms & Conditions:

| S. No. | Particulars | Quantity |
|--------|--------------------------------------|---|
| 1. | Payment Terms | 100% on receipt and acceptance of goods by the consignee at destination and on production of all required documents by the supplier. <u>Warranty certificate (if applicable) and NEFT/RTGS details shall be furnished along with invoice.</u> |
| 2. | Price | Price should be inclusive of all taxes & duties. |
| 3. | Freight | Shall be included in quoted price |
| 4. | Packing & Forwarding | Shall be included in quoted price |
| 5. | Delivery Terms | DAP, Bank Note Paper Mill India Private Limited, Mysore |
| 6. | Warranty Period | |
| 7. | Warranty Certificate | Applicable / Not Applicable |
| 8. | Delivery Period | |
| 9. | Material to be delivered at | Engineering Stores Bank Note Paper Mill India Private Limited Note Mudran Nagar Mysore 570 003 |
| 10. | Contact person in Engineering Stores | Mr. Ashutosh Kumar 0821 2401 486 Mr. Sunil Kumar 0821 2401 485 |



3. Price Bid Format :

| S. No. | Description | Qty. | UOM | Unit rate | Freight, P&F Charges | GST@..... | Unit rate including all taxes & charges | Grand total inclusive of all taxes and charges (DAP, BNPM, Mysore) |
|--------|--|------|-----|-----------|----------------------|-----------|---|--|
| 1 | Vacuum Gauge ½”BSP (M) Range - 1 to 1 bar Dial size: 4” Dual Scale (mm Hg and bar) MOC: wetted parts, body and cover SS316 Connection type: Back mount With glycerine | 04 | Nos | | | | | |
| 2 | Pressure Gauge ½”BSP (M) Range 0 to 100m bar Dial size: 4” MOC: wetted parts, body and cover SS316 Connection type: Bottom entry Without Glycerine | 4 | Nos | | | | | |
| 3 | Compound Gauge ½”BSP (M) Range - 100 to 800Kpa Dial size: 4” Dual Scale (mm Hg and bar) MOC: wetted parts, body and cover SS316 Connection type: Bottom Entry Without glycerine | 2 | Nos | | | | | |



| | | | | | | | | |
|---|---|---|-----|--|--|--|--|--|
| 4 | Vacuum Gauge ½”BSP (M) Range – 10.0 to 0mbar Dial size: 6” Dual Scale (mm Hg and bar) MOC: wetted parts, body and cover SS316 Connection type: Back mount Without glycerine | 2 | Nos | | | | | |
| 5 | Compound Gauge ½”BSP (M) Range – 600.0 to 1000mm WC Dial size: 4” Dual Scale (mm Hg and bar) MOC: wetted parts, body and cover SS316 Connection type: Bottom Entry Without glycerine | 2 | Nos | | | | | |
| 6 | Pressure Gauge ½”BSP (M) Range 0 to 10 kg/cm2 Dial size: 4” MOC: wetted parts, body and cover SS316 Connection type: Bottom entry Without Glycerine | 2 | Nos | | | | | |
| 7 | Pressure Gauge ½”BSP (M) Range 0 to 160 bar Dial size: 4” MOC: wetted parts, body and cover SS316 Connection type: Back mount With glycerine | 5 | Nos | | | | | |



| | | | | | | | | |
|----|--|---|-----|--|--|--|--|--|
| 8 | Pressure Gauge ¼ "BSP (M) Range 0 to 40 bar Dial size: 4" MOC: wetted parts, body and cover SS316 Connection type: Back mount With glycerine | 5 | Nos | | | | | |
| 9 | Pressure Gauge ¼ "BSP (M) Range 0 to 280 kg/cm2 Dial size: 2.5" MOC: wetted parts, body and cover SS316 Connection type: Bottom entry With Glycerine | 2 | Nos | | | | | |
| 10 | Pressure Gauge ¼ "BSP (M) Range 0 to 28 kg/cm2 Dial size: 4" MOC: wetted parts, body and cover SS316 Connection type: Bottom entry With Glycerine | 2 | Nos | | | | | |
| 11 | Pressure Gauge ¼ "BSP (M) Range 0 to 2.5 bar Dial size: 4" MOC: wetted parts, body and cover SS316 Connection type: Back Mount With Glycerine | 5 | Nos | | | | | |
| 12 | Vacuum Gauge ½" "BSP (M) Range -760 to 0 mm HG | 2 | Nos | | | | | |



| | | | | | | | | |
|----|---|---|-----|--|--|--|--|--|
| | Dial size: 4" Dual Scale (mm Hg and bar) MOC: wetted parts, body and cover SS316 Connection type: Back Mount With Glycerine | | | | | | | |
| 13 | Pressure Gauge ½" BSP (M) Range 0 to 56 Kg/cm2 Dial size: 4" MOC: wetted parts, body and cover SS316 Connection type: Back Mount With Glycerine | 2 | Nos | | | | | |
| 14 | Pressure Gauge ¼" BSP (M) Range 0 to 10 mpa Dial size: 2" MOC: wetted parts, body and cover SS316 Connection type: Back Mount With Glycerine | 5 | Nos | | | | | |
| 15 | Pressure Gauge ¼" BSP (M) Range 0 to 25m Bar Dial size: 4" MOC: wetted parts, body and cover SS316 Connection type: Back Mount(Panel Mounted) Without Glycerine | 5 | Nos | | | | | |
| | Grand Total | | | | | | | |
| | Grand Total In Words | | | | | | | |



Approved Makes:- Wika/ Protais/ Vigil/ Festo/ Baumer/ General

We hereby confirm that

1. We accept all terms & conditions mentioned in the enquiry.
2. Price quoted is inclusive of all taxes, duties, P&F, freight etc. on DAP, BNPM, Mysore basis.

Signature of bidder:.....

Name of the Firm:.....

Seal of the firm:

